

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.05.2016

Revision: 06.09.2011

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** BullFrog 93692 Lubricant & Rust Blocker Aerosol
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Corrosion inhibitors
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

Cortec Corporation
4119 White Bear Parkway
St. Paul, MN 55110 USA
Phone (651) 429-1100
Fax (651) 429-1122

- **Information department:** regulatory@cortecvci.com
- **1.4 Emergency telephone number:**
Spill, Leak, Fire, Exposure, or Accident
24 hour CHEMTREC contact:
USA and Canada 1-800-424-9300
International +1-703-527-3887 (collect calls accepted)
UK +(44)-870-8200418

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS08

- **Signal word** Danger
- **Hazard-determining components of labelling:**
Distillates (petroleum), hydrotreated light
- **Hazard statements**
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.05.2016

Revision: 06.09.2011

Trade name: BullFrog 93692 Lubricant & Rust Blocker Aerosol

(Contd. of page 1)

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P251 Do not pierce or burn, even after use.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains 2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol. May produce an allergic reaction.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

- Description:** Mixture of the substances listed below with nonhazardous additions.

Ingredients:

CAS: 75-28-5 EINECS: 200-857-2	isobutane ⚠ Flam. Gas 1, H220; ⚠ Press. Gas C, H280	10-25%
CAS: 74-98-6 EINECS: 200-827-9	propane liquefied ⚠ Flam. Gas 1, H220; ⚠ Press. Gas C, H280	10-25%
CAS: 64742-47-8 EINECS: 265-149-8	Distillates (petroleum), hydrotreated light ⚠ Asp. Tox. 1, H304	10-25%
CAS: 27136-73-8 EINECS: 248-248-0	2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol ⚠ Skin Corr. 1C, H314; ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400; ⚠ Aquatic Chronic 1, H410; ⚠ Acute Tox. 4, H302; ⚠ Skin Sens. 1, H317	≤ 2.5%

Additional information

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- After inhalation** Supply fresh air; consult doctor in case of complaints.
- After skin contact** Immediately wash with water and soap and rinse thoroughly.
- After eye contact** Rinse opened eye for several minutes under running water.
- After swallowing** If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- Information for doctor** Show this safety data sheet to the doctor in attendance.
- 4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media
Suitable extinguishing agents


CO₂, sand, extinguishing powder. Do not use water.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.05.2016

Revision: 06.09.2011

Trade name: BullFrog 93692 Lubricant & Rust Blocker Aerosol

(Contd. of page 2)

- **For safety reasons unsuitable extinguishing agents**
Water.
Water with full jet.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**



Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- **6.4 Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

- **Information about protection against explosions and fires:**



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Use explosion-proof apparatus / fittings and spark-proof tools.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

Observe official regulations on storing packagings with pressurised containers.

- **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidising agents.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.05.2016

Revision: 06.09.2011

Trade name: BullFrog 93692 Lubricant & Rust Blocker Aerosol

(Contd. of page 3)

- Do not gas tight seal receptacle.
- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **8.1 Control parameters**

- **Components with limit values that require monitoring at the workplace:**

75-28-5 isobutane (19-20%)

OEL	Short-term value: 22 mg/m ³ , 6 ppm
	Long-term value: 7.4 mg/m ³ , 2 ppm

74-98-6 propane liquefied (15-16%)

OEL	Short-term value: 22 mg/m ³ , 6 ppm
	Long-term value: 7.4 mg/m ³ , 2 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment**

- **General protective and hygienic measures**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.

- **Breathing equipment:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**

I.E., Nitrile, Viton, Neoprene
Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Protective Gloves** I.E., Nitrile, Viton, Neoprene

- **Eye protection:** Tightly sealed goggles.

- **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.05.2016

Revision: 06.09.2011

Trade name: BullFrog 93692 Lubricant & Rust Blocker Aerosol

(Contd. of page 4)

· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/Melting range:	undetermined
Boiling point/Boiling range:	-44 °C (*)
· Flash point:	-97 °C (*)
· Flammability (solid, gaseous)	Not applicable.
· Ignition temperature:	210 °C (*)
· Decomposition temperature:	Not determined.
· Self igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits: Lower:	0.5 Vol % (*)
Upper:	10.9 Vol % (*)
· Vapour pressure at 20 °C:	8300 hPa (*)
· Density at 20 °C:	0.905 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity: dynamic:	Not determined.
kinematic:	Not determined.
· 9.2 Other information	The above data are typical values and do not constitute a specification. *Properties have been calculated.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.05.2016

Revision: 06.09.2011

Trade name: BullFrog 93692 Lubricant & Rust Blocker Aerosol

(Contd. of page 5)

- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

64742-47-8 Distillates (petroleum), hydrotreated light

LC50 | 2.9 mg/l (Oncorhynchus mykiss (rainbow trout)) (96 hours)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

The European Waste Catalogue (EWC) waste codes do not refer to product but to origin. The manufacturer is therefore unable to quote a waste code for products which are used in various industries. Any codes shown should be regarded as a recommendation to the user.

· Uncleaned packagings:

- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA

UN1950

· 14.2 UN proper shipping name

· ADR

1950 AEROSOLS

· IMDG

AEROSOLS

· IATA

AEROSOLS, flammable

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.05.2016

Revision: 06.09.2011

Trade name: BullFrog 93692 Lubricant & Rust Blocker Aerosol

(Contd. of page 6)

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.
· Label 2.1

· IMDG, IATA



· Class 2.1
· Label 2.1

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user

Warning: Gases.
· Danger code (Kemler): -
· EMS Number: F-D,S-U
· Segregation groups Alkalis
· Stowage Code SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L
· Excepted quantities (EQ) Code: E0
Not permitted as Excepted Quantity
· Transport category 2
· Tunnel restriction code D

· IMDG

· Limited quantities (LQ) 1L
· Excepted quantities (EQ) Code: E0
Not permitted as Excepted Quantity

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.05.2016

Revision: 06.09.2011

Trade name: BullFrog 93692 Lubricant & Rust Blocker Aerosol

(Contd. of page 7)

· **UN "Model Regulation":** UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **National regulations**

· **Technical instructions (air):**

Class	Share in %
NK	16.5

· **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Cortec Corporation does not warranty any translation of this SDS not created by Cortec Corporation.

· **Relevant phrases**

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LD50: Lethal dose, 50 percent

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

LC50: Lethal concentration, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.05.2016

Revision: 06.09.2011

Trade name: BullFrog 93692 Lubricant & Rust Blocker Aerosol

(Contd. of page 8)

Press. Gas C: Gases under pressure – Compressed gas
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

GB