

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/17/2024

Reviewed on 01/17/2024

## 1 Identification

- **Product identifier**
- **Trade name:** **BullFrog® 93692 Lubricant & Rust Blocker Aerosol**
- **Application of the substance / the mixture** Corrosion inhibitors
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Cortec Corporation  
4119 White Bear Parkway  
St. Paul, MN 55110 USA  
Phone (651) 429-1100  
Fax (651) 429-1122
- **Information department:** compliance@cortecvci.com
- **Emergency telephone number:**  
Spill, Leak, Fire, Exposure, or Accident  
24 hour CHEMTREC contact:  
USA and Canada 1-800-424-9300  
International +1-703-527-3887 (collect calls accepted)

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Aerosols 1

H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Gases under Pressure - Compressed gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Aspiration Hazard 1

H304 May be fatal if swallowed and enters airways.



GHS07

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS04



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Distillates (petroleum), hydrotreated light

(Contd. on page 2)

USA

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/17/2024

Reviewed on 01/17/2024

**Trade name: BullFrog® 93692 Lubricant & Rust Blocker Aerosol**

(Contd. of page 1)

2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol

- **Hazard statements**

- H222 Extremely flammable aerosol.
- H280 Contains gas under pressure; may explode if heated.
- H317 May cause an allergic skin reaction.
- H304 May be fatal if swallowed and enters airways.

- **Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves.
- P301+P310 If swallowed: Immediately call a poison center/doctor.
- P321 Specific treatment (see first aid statements on this label).
- P331 Do NOT induce vomiting.
- P302+P352 If on skin: Wash with plenty of water.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- P405 Store locked up.
- P410+P403 Protect from sunlight. Store in a well-ventilated place.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

74-98-6	propane liquefied	10-25%
75-28-5	2-methylpropane	10-25%
64742-47-8	Distillates (petroleum), hydrotreated light	10-25%
27136-73-8	2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol	≥0.1-<1%

- **Additional information**

In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR 1910.1200), the specific chemical identity and/or exact percentage composition has been withheld as a trade secret.

For the wording of the listed hazard phrases refer to section 16.

### 4 First-aid measures

- **Description of first aid measures**

- **After inhalation**

Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably on side position for transportation.

- **After skin contact**

Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.

(Contd. on page 3)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/17/2024

Reviewed on 01/17/2024

**Trade name: BullFrog® 93692 Lubricant & Rust Blocker Aerosol**

(Contd. of page 2)

- **After eye contact** Rinse opened eye for several minutes under running water.
- **After swallowing**  
DO NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. If affected person is fully conscious, give one glass of water to drink. Never give anything by mouth to an unconscious person. Get immediate medical attention.
- **Information for doctor** Show this safety data sheet to the doctor in attendance.
- **Most important symptoms and effects, both acute and delayed**  
The symptoms and effects are as expected from the hazards shown in section 2. No specific product related symptoms are known.  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**  
In certain fire conditions, traces of other toxic gases cannot be excluded.
- **Advice for firefighters** Self-contained breathing apparatus
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Wear fully protective suit.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**



Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- **Handling**
- **Precautions for safe handling**  
Store in cool, dry place in tightly closed receptacles.  
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)

USA

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/17/2024

Reviewed on 01/17/2024

Trade name: BullFrog® 93692 Lubricant &amp; Rust Blocker Aerosol

(Contd. of page 3)

- **Information about protection against explosions and fires:**



Keep ignition sources away - Do not smoke.

Protect from heat.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights.

Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Provide adequate precautions, such as electrical grounding and bonding.

- **Conditions for safe storage, including any incompatibilities**

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

Observe official regulations on storing packagings with pressurized containers.

- **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidizing agents.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

- **Storage class 2 B**

- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

### 74-98-6 propane liquefied (10-25%)

PEL	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
TLV	see Appendix F Minimal oxygen content ( D, EX)

### 75-28-5 2-methylpropane (10-25%)

TLV	Short-term value: 1000 ppm (EX)
-----	------------------------------------

### 64742-47-8 Distillates (petroleum), hydrotreated light (10-25%)

RCP-TWA	Long-term value: 1200 mg/m <sup>3</sup> Total Hydrocarbons
---------	---

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls** Use local exhaust ventilation to control airborne concentrations below exposure limits.

- **Personal protective equipment**

- **General protective and hygienic measures**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 5)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/17/2024

Reviewed on 01/17/2024

**Trade name: BullFrog® 93692 Lubricant & Rust Blocker Aerosol**

(Contd. of page 4)

**· Breathing equipment:**


Use suitable respiratory protective device in case of insufficient ventilation.

Suitable respiratory protective device recommended.

Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). To determine the appropriate type of respiratory protection that should be used, a hazard assessment should be performed prior to using the product. Environmental conditions such as ventilation and other contaminants may affect the type of respiratory protection that is chosen.

**· Protection of hands:**

I.E., Nitrile, Viton, Neoprene  
Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Protective Gloves** I.E., Nitrile, Viton, Neoprene

· **Eye protection:** Tightly sealed goggles.

· **Body protection:** Protective work clothing.

## 9 Physical and chemical properties

**· Information on basic physical and chemical properties**
**· General Information**
**· Appearance:**

<b>Form:</b>	Aerosol
<b>Color:</b>	According to product specification
<b>Odor:</b>	Characteristic
<b>Odor threshold:</b>	Not determined.

· **pH-value:** Not determined.

**· Change in condition**

<b>Melting point/Melting range:</b>	undetermined
<b>Boiling point/Boiling range:</b>	-44 °C (-47.2 °F) (*)

· **Flash point:** -97 °C (-142.6 °F) (\*)

· **Flammability (solid, gaseous)** Not applicable.

· **Auto igniting:** 210 °C (410 °F) (\*)

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Not determined.

**· Explosion limits:**

<b>Lower:</b>	0.5 Vol % (*)
<b>Upper:</b>	10.9 Vol % (*)

· **Vapor pressure at 20 °C (68 °F):** 8,300 hPa (6.200 mm Hg) (\*)

· **Density at 20 °C (68 °F):** 0.9-0.91 g/cm<sup>3</sup> (7.51-7.59 lbs/gal)

(Contd. on page 6)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/17/2024

Reviewed on 01/17/2024

**Trade name: BullFrog® 93692 Lubricant & Rust Blocker Aerosol**

(Contd. of page 5)

· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
dynamic:	Not determined.
kinematic:	Not determined.
· <b>Other information</b>	The above data are typical values and do not constitute a specification. *Properties have been calculated.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under recommended storage conditions
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid**  
Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.  
High temperatures, sparks, and open flames.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known

### 11 Toxicological information

#### · Information on toxicological effects

#### · Acute toxicity:

#### · LD/LC50 values that are relevant for classification:

#### 64742-47-8 Distillates (petroleum), hydrotreated light

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

#### · Primary irritant effect:

- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

#### · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant

#### · Carcinogenic categories

#### · IARC (International Agency for Research on Cancer)

	Tertiary alkanolamine	3
111-42-2	2,2'-iminodiethanol	2B

#### · NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/17/2024

Reviewed on 01/17/2024

**Trade name: BullFrog® 93692 Lubricant & Rust Blocker Aerosol**

(Contd. of page 6)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

**64742-47-8 Distillates (petroleum), hydrotreated light**

Oral	LL50	25 mg/l (Oncorhynchus mykiss (rainbow trout)) (96 hours)
	LC50	2.9 mg/l (Oncorhynchus mykiss (rainbow trout)) (96 hours)

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation** Dispose of in accordance with local, state, and federal regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

· **UN-Number**

· **DOT, ADR, IMDG, IATA** UN1950

· **UN proper shipping name**

· **DOT** Aerosols, flammable

· **ADR** 1950 AEROSOLS

· **IMDG** AEROSOLS

· **IATA** AEROSOLS, flammable

· **Transport hazard class(es)**

· **DOT**



· **Class** 2.1 Gases

(Contd. on page 8)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/17/2024

Reviewed on 01/17/2024

**Trade name: BullFrog® 93692 Lubricant & Rust Blocker Aerosol**

(Contd. of page 7)

· **Label** 2.1

· **ADR**



· **Class** 2.5F Gases  
 · **Label** 2.1

· **IMDG, IATA**



· **Class** 2.1 Gases  
 · **Label** 2.1

· **Packing group**  
 · **DOT, ADR, IMDG, IATA** not classified as dangerous goods

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Gases  
 · **Hazard identification number (Kemler code):** -  
 · **EMS Number:** F-D,S-U  
 · **Segregation groups** (SGG18) Alkalis  
 · **Stowage Code** SW1 Protected from sources of heat.  
 SW22 For AEROSOLS with a maximum capacity of 1 litre:  
 Category A. For AEROSOLS with a capacity above 1 litre:  
 Category B. For WASTE AEROSOLS: Category C, Clear of  
 living quarters.  
 · **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:  
 Segregation as for class 9. Stow "separated from" class 1 except  
 for division 1.4.  
 For AEROSOLS with a capacity above 1 litre:  
 Segregation as for the appropriate subdivision of class 2.  
 For WASTE AEROSOLS:  
 Segregation as for the appropriate subdivision of class 2.

· **Transport in bulk according to Annex II of  
 MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**  
 · **Excepted quantities (EQ)** Code: E0  
 Not permitted as Excepted Quantity

· **IMDG**  
 · **Limited quantities (LQ)** 1L  
 · **Excepted quantities (EQ)** Code: E0  
 Not permitted as Excepted Quantity

· **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

USA

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/17/2024

Reviewed on 01/17/2024

**Trade name: BullFrog® 93692 Lubricant & Rust Blocker Aerosol**

(Contd. of page 8)

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Sara**

· **SARA Section 355 (extremely hazardous substances)**

None of the ingredients is listed.

· **SARA Section 313 (specific toxic chemical listings)**

112-34-5	2-(2-butoxyethoxy)ethanol
111-42-2	2,2'-iminodiethanol
111-41-1	2-(2-aminoethylamino)ethanol

· **TSCA (Toxic Substances Control Act): (All ingredients are listed.)**

· **Hazardous Air Pollutants**

111-42-2	2,2'-iminodiethanol
----------	---------------------

· **Proposition 65**

· **Prop 65 - Chemicals known to cause cancer**

2,2'-iminodiethanol

· **Chemicals known to cause reproductive toxicity for females**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity**

None of the ingredients is listed.

· **Carcinogeny categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Canadian Domestic Substances List (DSL): (Substances not listed)**

All ingredients are listed.

· **Canadian Non-Domestic Substances List (NDSL): (Substances not listed)**

None of the ingredients is listed.

· **Philippines Inventory of Chemicals and Chemical Substances: (Substances not listed)**

All ingredients are listed.

· **Chinese Chemical Inventory of Existing Chemical Substances: (Substances not listed)**

All ingredients are listed.

· **Australian Inventory of Chemical Substances: (Substances not listed)**

All ingredients are listed.

· **New Zealand Inventory of Chemicals: (Substances not listed)**

All ingredients are listed.

· **Existing Chemical Substances**

propane liquefied	2-3
2-methylpropane	2-4

(Contd. on page 10)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/17/2024

Reviewed on 01/17/2024

**Trade name: BullFrog® 93692 Lubricant & Rust Blocker Aerosol**

(Contd. of page 9)

2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol

5-425, 5-3496

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02    GHS04    GHS07    GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**  
Distillates (petroleum), hydrotreated light  
2-(heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol
- **Hazard statements**  
H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H317 May cause an allergic skin reaction.  
H304 May be fatal if swallowed and enters airways.
- **Precautionary statements**  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves.  
P301+P310 If swallowed: Immediately call a poison center/doctor.  
P321 Specific treatment (see first aid statements on this label).  
P331 Do NOT induce vomiting.  
P302+P352 If on skin: Wash with plenty of water.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P363 Wash contaminated clothing before reuse.  
P405 Store locked up.  
P410+P403 Protect from sunlight. Store in a well-ventilated place.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Date of preparation / last revision** 01/17/2024
- **Abbreviations and acronyms:**  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
LC50: Lethal concentration, 50 percent

(Contd. on page 11)

USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/17/2024

Reviewed on 01/17/2024

**Trade name: BullFrog® 93692 Lubricant & Rust Blocker Aerosol**

(Contd. of page 10)

LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
Flammable Aerosols 1: Aerosols – Category 1  
Gases under Pressure - Compressed gas: Gases under pressure – Compressed gas  
Sensitization - Skin 1: Skin sensitisation – Category 1  
Aspiration Hazard 1: Aspiration hazard – Category 1

· **\* Data compared to the previous version altered.**

USA